




## Non Insulated Ring Term. DIN 46234



**DIN 46234  
BRAZED SEAM**

Part N°	Wire size mm <sup>2</sup>	Dimensions mm.			a	c	d1	"S" Material width	Treatment	
		Ød2	Ød3	l						
D-2.2-0.5	0.2-0.5	2.2	5.0	10.0	4.0	2.0	1.0	copper 0.5	Sn	1.000
D-2.7-0.5		2.7	5.0	10.0	4.0	2.0	1.0	copper 0.5	Sn	1.000
D-3.2-0.5		3.2	5.0	10.0	4.0	2.0	1.0	copper 0.5	Sn	1.000
D-3.7-0.5		3.7	6.0	12.0	4.0	2.0	1.0	copper 0.5	Sn	1.000
D-4.3-0.5		4.3	6.5	12.0	4.0	2.0	1.0	copper 0.5	Sn	1.000
D-5.3-0.5		5.3	8.0	12.0	4.0	2.0	1.0	copper 0.5	Sn	1.000
D-2.2-1	0.5-1.5	2.2	6.0	11.0	5.0	4.0	1.6	copper 0.8	Sn	1.000
D-2.7-1		2.7	6.0	11.0	5.0	4.0	1.6	copper 0.8	Sn	1.000
D-3.2-1		3.2	6.0	11.0	5.0	4.0	1.6	copper 0.8	Sn	1.000
D-3.7-1		3.7	6.0	11.0	5.0	4.0	1.6	copper 0.8	Sn	1.000
D-4.3-7-1		4.3	7.0	11.5	5.0	4.0	1.6	copper 0.8	Sn	1.000
D-4.3-1		4.3	8.0	12.0	5.0	4.0	1.6	copper 0.8	Sn	1.000
D-5.3-8-1		5.3	8.0	12.5	5.0	4.0	1.6	copper 0.8	Sn	1.000
D-5.3-1		5.3	10.0	13.0	5.0	4.0	1.6	copper 0.8	Sn	1.000
D-6.5-10-1		6.5	10.0	13.0	5.0	4.0	1.6	copper 0.8	Sn	1.000
D-6.5-1		6.5	11.0	15.0	5.0	4.0	1.6	copper 0.8	Sn	1.000
D-8.4-1		8.4	14.0	17.0	5.0	4.0	1.6	copper 0.8	Sn	1.000
D-10.5-14-1		10.5	14.0	17.0	5.0	4.0	1.6	copper 0.8	Sn	1.000
D-10.5-18-1		10.5	18.0	19.0	5.0	4.0	1.6	copper 0.8	Sn	1.000


# Non Insulated Ring Terminals DIN 46234



Part N°	Wire size mm <sup>2</sup>	Dimensions mm.			a	c	d1	"S" Material width	Treatment	☐
		Ød2	Ød3	l						
D-3.2-2.5	1.5-2.5	3.2	6.0	11.0	5.0	4.5	2.3	copper 0.8	Sn	1.000
D-3.7-2.5		3.7	6.0	11.0	5.0	4.5	2.3	copper 0.8	Sn	1.000
D-4.3-6.8-2.5		4.3	6.8	11.6	5.0	4.5	2.3	copper 0.8	Sn	1.000
D-4.3-2.5		4.3	8.0	12.0	5.0	4.5	2.3	copper 0.8	Sn	1.000
D-5.3-8.0-2.5		5.3	8.0	13.5	5.0	4.5	2.3	copper 0.8	Sn	1.000
D-5.3-2.5		5.3	10.0	14.0	5.0	4.5	2.3	copper 0.8	Sn	1.000
D-6.5-2.5		6.5	11.0	16.0	5.0	4.5	2.3	copper 0.8	Sn	1.000
D-8.4-2.5		8.4	14.0	17.0	5.0	4.5	2.3	copper 0.8	Sn	1.000
D-10.5-15-2.5		10.5	15.0	17.0	5.0	4.5	2.3	copper 0.8	Sn	1.000
D-10.5-18-2.5		10.5	18.0	18.5	5.0	4.5	2.3	copper 0.8	Sn	1.000
D-13.0-2.5		13.0	18.0	20.0	5.0	4.5	2.3	copper 0.8	Sn	1.000
D-4-6	2.5-6	4.3	8.0	14.0	6.0	6.0	3.6	copper 1.0	Sn	1.000
D-5-6		5.3	10.0	15.0	6.0	6.0	3.6	copper 1.0	Sn	1.000
D-6-6		6.5	11.0	16.0	6.0	6.0	3.6	copper 1.0	Sn	1.000
D-8-6		8.4	14.0	19.0	6.0	6.0	3.6	copper 1.0	Sn	1.000
D-10-6		10.5	18.0	21.0	6.0	6.0	3.6	copper 1.0	Sn	500
D-12-6		13.0	18.0	21.0	6.0	6.0	3.6	copper 1.0	Sn	500
D-5-10	10	5.3	10.0	16.0	8.0	8.0	4.5	copper 1.1	Sn	500
D-6-10		6.5	11.0	17.0	8.0	8.0	4.5	copper 1.1	Sn	500
D-8-10		8.4	14.0	20.0	8.0	8.0	4.5	copper 1.1	Sn	500
D-10-10		10.5	18.0	21.0	8.0	8.0	4.5	copper 1.1	Sn	500
D-12-10		13.0	22.0	23.0	8.0	8.0	4.5	copper 1.1	Sn	500
D-5-16	16	5.3	11.0	20.0	10.0	10.5	5.8	copper 1.2	Sn	500
D-6-16		6.5	11.0	20.0	10.0	10.5	5.8	copper 1.2	Sn	500
D-8-16		8.4	14.0	22.0	10.0	10.5	5.8	copper 1.2	Sn	500
D-10-16		10.5	18.0	24.0	10.0	10.5	5.8	copper 1.2	Sn	500
D-12-16		13.0	22.0	26.0	10.0	10.5	5.8	copper 1.2	Sn	250
D-5-25	25	5.3	12.0	25.0	11.0	12.0	7.5	copper 1.5	Sn	50
D-6-25		6.5	12.0	25.0	11.0	12.0	7.5	copper 1.5	Sn	50
D-8-25		8.4	16.0	25.0	11.0	12.0	7.5	copper 1.5	Sn	50
D-10-25		10.5	18.0	26.0	11.0	12.0	7.5	copper 1.5	Sn	50
D-12-25		13.0	22.0	31.0	11.0	12.0	7.5	copper 1.5	Sn	50
D-16-25		17.0	28.0	35.0	11.0	12.0	7.5	copper 1.5	Sn	50

# Non Insulated Ring Terminals DIN 46234



Part N°	Wire size mm <sup>2</sup>	Dimensions mm.			a	c	d1	"S" Material width	Treatment	
		Ød2	Ød3	l						
D-6-35	35	6.5	15.0	26.0	12.0	15.0	9.0	copper 1.6	Sn	50
D-8-35		8.4	16.0	26.0	12.0	15.0	9.0	copper 1.6	Sn	50
D-10-35		10.5	18.0	27.0	12.0	15.0	9.0	copper 1.6	Sn	50
D-12-35		13.0	22.0	31.0	12.0	15.0	9.0	copper 1.6	Sn	50
D-16-35		17.0	28.0	36.0	12.0	15.0	9.0	copper 1.6	Sn	50
D-6-50	50	6.5	18.0	34.0	16.0	17.0	11.0	copper 1.8	Sn	50
D-8-50		8.4	18.0	34.0	16.0	17.0	11.0	copper 1.8	Sn	50
D-10-50		10.5	18.0	34.0	16.0	17.0	11.0	copper 1.8	Sn	50
D-12-50		13.0	22.0	36.0	16.0	17.0	11.0	copper 1.8	Sn	50
D-16-50		17.0	28.0	40.0	16.0	17.0	11.0	copper 1.8	Sn	50
D-6-70	70	6.5	22.0	38.0	18.0	21.0	13.0	copper 2.0	Sn	50
D-8-70		8.4	22.0	38.0	18.0	21.0	13.0	copper 2.0	Sn	50
D-10-70		10.5	22.0	38.0	18.0	21.0	13.0	copper 2.0	Sn	50
D-12-70		13.0	22.0	38.0	18.0	21.0	13.0	copper 2.0	Sn	50
D-16-70		17.0	28.0	42.0	18.0	21.0	13.0	copper 2.0	Sn	50
D-8-95	95	8.4	24.0	42.0	20.0	23.0	15.0	copper 2.5	Sn	25
D-10-95		10.5	24.0	42.0	20.0	23.0	15.0	copper 2.5	Sn	25
D-12-95		13.0	24.0	42.0	20.0	23.0	15.0	copper 2.5	Sn	25
D-16-95		17.0	28.0	44.0	20.0	23.0	15.0	copper 2.5	Sn	25
D-8-120	120	8.4	24.0	44.0	22.0	24.0	16.5	copper 3.0	Sn	25
D-10-120		10.5	24.0	44.0	22.0	24.0	16.5	copper 3.0	Sn	25
D-12-120		13.0	24.0	44.0	22.0	24.0	16.5	copper 3.0	Sn	25
D-16-120		17.0	28.0	48.0	22.0	24.0	16.5	copper 3.0	Sn	25
D-10-150	150	10.5	30.0	50.0	24.0	28.0	19.0	copper 3.2	Sn	25
D-12-150		13.0	30.0	50.0	24.0	28.0	19.0	copper 3.2	Sn	25
D-16-150		17.0	30.0	50.0	24.0	28.0	19.0	copper 3.2	Sn	25
D-10-185	185	10.5	36.0	50.0	28.0	33.0	21.0	copper 3.5	Sn	25
D-12-185		13.0	36.0	50.0	28.0	33.0	21.0	copper 3.5	Sn	25
D-16-185		17.0	36.0	50.0	28.0	33.0	21.0	copper 3.5	Sn	25
D-10-240	240	10.5	38.0	56.0	32.0	36.0	23.5	copper 4.0	Sn	25
D-12-240		13.0	38.0	56.0	32.0	36.0	23.5	copper 4.0	Sn	25
D-16-240		17.0	38.0	56.0	32.0	36.0	23.5	copper 4.0	Sn	25