





Terminales horquilla



**Ranura
soldada**

Material: Cobre
Acabado: Estañado

Ref.	Sección cable mm ² / AWG	Dimensiones mm.			
		Ød2	B	L	
0.5Y-3	0,5	3,2	5,2	12,4	1.000
0.5Y-3.5	0,2-0,5	3,7	6,6	14,0	
0.5Y-4	22-20	4,3	6,6	14,0	
1.25Y-3	1,25	3,2	5,7	16,0	1.000
1.25Y-3.5S	0,25-1,65	3,7	5,7	16,0	
1.25Y-3.5	22-16	3,7	6,2	16,0	
1.25Y-4S		4,3	6,4	16,0	
1.25Y-4		4,3	7,2	16,0	
1.25Y-5		5,3	8,0	16,0	
1.25Y-6		6,4	10,7	17,0	
2Y-3	2	3,2	5,7	16,0	1.000
2Y-3.5S	1,04-2,63	3,7	5,7	16,0	
2Y-3.5	16-14	3,7	6,2	16,0	
2Y-4S		4,3	6,4	16,0	
2Y-4		4,3	7,2	16,0	
2Y-5		5,3	8,0	16,0	
2Y-6		6,4	10,7	17,0	
3.5Y-4	3,5	4,3	8,0	18,0	1.000
3.5Y-5	2,63-4,6	5,3	9,5	18,0	
	12				
5.5Y-3	5,5	3,2	7,3	19,5	1.000
5.5Y-3.5	2,63-6,64	3,7	8,1	19,5	
5.5Y-4S	12-10	4,3	6,3	19,5	
5.5Y-4		4,3	8,2	19,5	
5.5Y-5		5,3	9,0	19,5	
5.5Y-6		6,4	12,0	23,1	
8Y-5	8	5,3	10,9	27,0	1.000
8Y-6	6,64-10,52	6,4	10,9	27,0	
	8				